

## GEN - SETS CUMMINS – prime power



<i>All gen-sets AMP CM</i>				
<i>- 50 Hz</i>				
<i>- 400/230V</i>				
<i>- 1.500 RPM</i>				
<i>Model</i>	<i>Engine type</i>	<i>kVA cos. 0,8</i>	<i>Netto kWe</i>	<i>Diesel fuel consumption at 75% load</i>
AMP CM 28	4B3.3G1	35	28	6 l/h
AMP CM 50	4BT3.3G2	63	50	11 l/h
AMP CM 76	4BTA3.3G4	95	76	16 l/h
AMP CM 109	6BTA5.9G3	136	109	24 l/h
AMP CM 160	6CTAA8.3G3	200	160	34 l/h
AMP CM 256	NT855G8	320	256	52 l/h
AMP CM 400	QSX15G8	500	400	79 l/h
AMP CM 644	QSK23G3	805	644	121 l/h
AMP CM 800	QST30G4	1000	800	151 l/h
AMP CM 1120	KTA50G8	1400	1120	222 l/h
AMP CM 1555	QSK60GS3	1944	1555	311 l/h

All gen-sets are equipped with:

- Alternators EE Cummins Newage Stamford
- Controlers Altronic
- Stainless steel fuel tanks
- Stainless steel exhaust gases sylencers